



Ø DN	L	Ø D	Ø k	Ø d4	b	f	n	Ø d2	H	Gewicht
(mm)										(kg)
PN 16										
50	200	165	125	102	18	3	4	18	147	14
65	240	185	145	122	18	3	4	18	161	19
80	260	200	160	138	20	3	8	18	178	26
100	300	220	180	158	20	3	8	18	190	34
125	350	250	210	188	22	3	8	18	265	46
150	400	285	240	212	22	3	8	22	285	70
200	500	340	295	268	24	3	12	22	345	104
250	600	405	355	320	26	3	12	26	394	190
300	700	460	410	378	28	4	12	26	420	280
PN 40										
40	200	150	110	88	18	3	4	18	135	12
50	230	165	125	102	20	3	4	18	147	15
65	290	185	145	122	22	3	8	18	161	21
80	310	200	160	138	24	3	8	18	178	28
100	350	235	190	162	24	3	8	22	190	40
125	400	270	220	188	26	3	8	26	265	59
150	480	300	250	218	28	3	8	26	285	77
200	600	375	320	285	34	3	12	30	332	160
250	730	450	385	345	38	3	12	33	395	308
300	850	515	450	410	42	4	16	33	420	452

Item	Parts name	Bezeichnung	Material
1	Body	Gehäuse	GS-C25N +13Cr
2	Disc	Klappenscheibe	GS-C25N
3	Disc Nut	Haltemutter	1.1181
4	Arm	Klappenhebel	GS-C25N
5	Arm Pin	Klappenhebelstift	A276 410
6	Cover Bolt	Deckelschraube	A193 B7
7	Cover Nut	Deckelmuttern	A194 2H
8	Bonnet Gasket	Deckeldichtung	Graphite SS304
9	Cover	Deckel	GS-C25N
10	Eyebolts	Ringschraube	1.7711
11	Plug	Halteschraube	A194 2H

Face-to-face dimensions/Baulänge: DIN EN 558-1 Reihe 48		EN 10204	Design by: DZ	Checked by: RS	Date: 31/05/17
Type: Rückschlagklappe Typ OPAL					
Class/Druckstufe: PN 16 - 40		Size/Nennweite: DN 40 - 300			
Flanged ends dimensions/Flanschmaße: DIN 2526			Rev: 1		

kihsco
Valves Europe GmbH